

Secure Touch



Specifications

Appearance

Processor	A9, Dual Core 1.2GHz
Memory	1GB RAM, 8GB FLASH, Ext. TF Slot
OS	Android 4.2.2
Display	7", TFT 800*480
Keypad	12 alphanumeric keys, 7 function keys
SIM Slots	1 (Standard), 2 (Optional)
Communications	3G Module (Module SIM 5360E), WCDMA 900/2100MHz, GSM 850/900/1800/1900 MHz, WIFI, LAN, Dialup – Required communication module will be provided.
2D Bar Code Scanner	2D Bar Code Reader and QR Code Reader (Optional)
Peripheral Ports	2 USB Host, 1 Micro USB (OTG), RJ 45, RJ 11 (Optional)
Digital Audio synthesizer	Built-in speaker
Built-in Fingerprint Module	ISO 19794 & ANSI_378 Supported
Buzzer single tone beeper	Optional
Smart card reader, ISO 7816	Optional
Contactless card reader, ISO14443 Type A/B, Mifare®	Optional
GPS	Optional
Printer	Thermal graphic printer; Speed: 18 lines/sec; Paper width: 58mm (Optional)
Power Supply	Input:100-240VAC, 50Hz/60Hz,1.0A;output:12VDC, 2A
Camera for Person Picture	5 Mega Pixel, Fixed Focus (Optional)
Battery: Lithium Polymer rechargeable battery	7.4V, 2500mA, Li-ion (Standard), 5000mA & 10000mA (Optional)
Magnetic card reader, Track 1/2/3, bi-directional swipe, ISO7810, ISO7811, ISO7812	Optional
Dimensions(mm)	290(L)×219(W)×85(H)
Weight	1500g
Certification	CE, Pakistan Telecom Authority Type Approved
Working Environment:	Temperature:0°C~50°C; R.H.: 10%~90% (non-condensing)
Storage Environment:	Temperature:-20°C~70°C; R.H.: 5%~95% (non-condensing)



Note:

The Fingerprint Scanner in the device will be either Futronic Model FS81 or Dermalog Model F1,